

# IXP12EB Intel® IXP1200 Network Processor Ethernet Evaluation Kit

[developer.intel.com/  
design/network](http://developer.intel.com/design/network)

## Product Highlights


- Evaluation platform for the IXP1200 Network Processor
- Optimized in a wire-speed, store-and-forward configuration
- Eight-port 10/100 Ethernet controller
- Two-port Gigabit Ethernet controller
- SRAM and SDRAM subsystems
- Serial port
- Supports IXP12DE software development environment
- Software libraries
- Sample application code, boot code and diagnostics
- Device drivers, route and bridge table managers
- Board support package for WindRiver\* VxWorks\*

## Product Overview

The IXP12EB Ethernet Evaluation Kit is a powerful tool for developing and verifying hardware and software for the IXP1200 Network Processor, the cornerstone of the Intel® Internet Exchange™ (IX) architecture. The kit supports the IXP12DE software development environment for programming the Network Processor's microengines and integrated Intel® StrongARM\* processor core. This enables developers to write, assemble and optimize, debug and verify symbolic microcode using IXP1200 Network Processor hardware.

The hardware design is optimized in a wire-speed, store-and-forward configuration. It enables system simulation in conjunction with a host system (typically a network-based PC) to validate data paths, chip functionality, system functionality, device driver behavior, and functionality of board support package software.

The IXP12EB Ethernet Evaluation Kit includes a PCI form factor board based on the IXP1200 Network Processor. The PCI board has eight



10/100 Mbps ports and two Gigabit Ethernet ports. The kit also includes a passive PCI back-plane and an Ethernet Network Interface Card (NIC) that enables the system's host processor to communicate efficiently to the IXP1200 Network Processor. All three boards are housed and shipped in a 4U chassis.

The IXP12EB kit simplifies evaluation of the following characteristics:

- IXP1200 Network Processor functionality in a network wire-speed store-and-forward configuration.
- Use of the IXP1200 Network Processor as a network switch solution to perform bridging and routing functions with multiple 10/100 Mbps and Gigabit Ethernet ports.
- Performance capabilities of a single IXP1200 Network Processor running example network code. The kit will process and forward at wire speed (approximately three million packets/sec.) using Layer 2 and Layer 3 packet inspection on minimum-size packets, and a longest-prefix match algorithm.
- Electrical, mechanical, and component layouts used in a typical IXP1200 Network Processor design. The evaluation kit design illustrates how to interface various devices to the IXP1200 Network Processor via the IX Bus, providing a design reference for developers using the IXP1002 Dual-Port Gigabit Ethernet media access controller (MAC) and the 21440AD 8-Port 10/100 Mbps Ethernet controller.

## Programming the IXP1200 Network Processor

## IXP12EB Block Diagram

## Versatile Applications

---

The diagram illustrates the architecture of the IXP1200 Network Processor. It is shown as a large teal block containing several components:
 

- Level One™ 10/100 PHY**: Two orange blocks at the top, connected to the IXP1200 processor.
- Gig PHY**: Two yellow blocks on the left, connected to the IXP1200 processor.
- IXF1002** and **21440**: Two purple blocks in the middle, connected to the IXP1200 processor.
- IXP1200 Network Processor**: A large blue block at the bottom of the teal area, which is the central processing unit.

 Below the teal block, a large grey double-headed arrow labeled **Passive PCI Back Plane** connects to a smaller teal block containing the **Intel 82559** network controller.

## Intel® Pro/100+ Management Adapter

## Features and Benefits

### Hardware Features

### Benefits

<b>IXP1200 Network Processor</b>	An advanced network forwarding engine that is both powerful and flexible
<b>21440AD 8-Port 10/100 Mbps Ethernet Controller</b>	Provides eight 10/100 Mbps Ethernet ports/slow ports
<b>IXF1002 Dual Port Gigabit Ethernet Controller</b>	Provides two Gigabit Ethernet ports/fast ports
<b>Micron MT58LC128K32C6LG-6.6 SSRAM Micron MT58LC256K32C6LG-6.6 SSRAM</b>	SSRAM contains lookup tables and buffers free-lists for processing cells, frames, and packets
<b>SRAM Subsystem</b>	
<b>Intel Flash 28F800B3B-90</b>	Reliable system boot capability
<b>Micron's 64 Meg Synchronous DRAM (SDRAM) 1 Meg x 16 x 4 Micron MT48LC16M4A2TG-8E</b>	SDRAM memory contains large data structures such as packet/cell/frame data and forwarding table information. It also holds the StrongARM® processor core instruction code space during runtime
<b>SDRAM Subsystem</b>	
<b>Serial Port</b>	Provides hardware debug capability or console interface—9600 Baud

### Software Features

### Benefits

<b>IXP12DE Network Processor Development Environment</b>	Software workbench for programming the IXP1200 Network Processor
<b>Software libraries</b>	Accelerated software development to help speed time-to-market
<b>Example application code</b>	
<b>Sample boot code and diagnostics</b>	
<b>Device drivers</b>	
<b>Route and bridge table managers</b>	
<b>Board support package for WindRiver VxWorks</b>	


## Specifications

Description	Specification
Regulatory Testing and Safety Approval	FCC Class A, CE
Physical Dimensions	(L) 28 7/8 in. x (W) 26 1/4 in. x (D) 13 3/8 in.
Weight	22 1/4 lbs.
Power	110 / 220 Volts (Selectable)
Operating Temperature	10°C to 32°C

## A New Approach to Development

The Intel IX Architecture is a comprehensive family of feature-rich silicon and software building blocks and tools that accelerates development of powerful, flexible network and communications products. The cornerstone of the Intel Internet Exchange Architecture is the Intel IXP1200 network processor—which combines the performance and programmability to develop intelligent, differentiated network solutions—at the speed of Internet growth.

For more information on Intel's family of Network Processor products, please visit <http://developer.intel.com/design/network>



## Intel Access

Developer's Site	<a href="http://developer.intel.com/">http://developer.intel.com/</a>
Networking Components Home Page	<a href="http://developer.intel.com/design/network">http://developer.intel.com/design/network</a>
Other Intel Support: Intel Literature Center	<a href="http://developer.intel.com/design/litcentr/">http://developer.intel.com/design/litcentr/</a> (800) 548-4725 7 a.m. to 7 p.m. CST (U.S. and Canada) International locations please contact your local sales office.
General Information Hotline	(800) 628-8686 or (916) 356-3104 5 a.m. to 5 p.m. PST

Information in this document is provided in connection with Intel products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life saving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice.

Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

\*Other brands and names are the property of their respective owners.



For more information, visit the Intel Web site at: [developer.intel.com](http://developer.intel.com)

**UNITED STATES AND CANADA**  
Intel Corporation  
Robert Noyce Bldg.  
2200 Mission College Blvd.  
P.O. Box 58119  
Santa Clara, CA 95052-8119  
USA

**EUROPE**  
Intel Corporation (UK) Ltd.  
Pipers Way  
Swindon  
Wiltshire SN3 1RJ  
UK

**ASIA-PACIFIC**  
Intel Semiconductor Ltd.  
32/F Two Pacific Place  
88 Queensway, Central  
Hong Kong, SAR

**JAPAN**  
Intel Kabushiki Kaisha  
P.O. Box 115 Tsukuba-gakuen  
5-6 Tokodai, Tsukuba-shi  
Ibaraki-ken 305  
Japan

**SOUTH AMERICA**  
Intel Semicondutores do Brasil  
Rue Florida, 1703-2 and CJ22  
CEP 04565-001 Sao Paulo-SP  
Brazil